

## Specification for Colorpoint (CP) 36oz

Construction:	Colorpoint
Yarn Content:	Zeftron Nylon
Dye Method:	Solution Dyed
Gauge:	1/10th
Width:	12'0"   15'0"(15ft is standard for RESERVE running line)
Yarn Weight Tufted:	36 oz
Stitch Rate:	12 SPI
Pile Heights:	approx. - low - .175 / high - .315
Primary Backing:	Woven Polypropylene
Secondary Backing:	Woven Polypropylene
Pattern Repeat:	TBD

---

### Performance

Flame Resistance:	Passes DOC FF-1-70
Static Control:	Less than 3.5 KV
Flooring Radiant Panel:	Class 1 (ASTM 648)
Smoke Density:	Less than .450 (ASTM E622)
Soil Resistance:	Commercial Anti-Soil Protection
Stain Resistance:	Commercial Stain Protection

---

### Warranties

Wear:	10 Year Limited
Static:	Lifetime Limited
Colorfastness:	Lifetime Limited

Tufted pile weight is based on material post production; pattern and shear amounts may alter final tufted pile weight.

All specifications subject to normal manufacturing tolerances.

Encore Hospitality flooring products are to be installed in full accordance with Encore's installation instructions and standard trade practices. A program of regular cleaning and maintenance is vital for retaining a high appearance level. Installation plus Care & Maintenance manuals can be downloaded at [www.encorecarpet.net](http://www.encorecarpet.net)