

Specification for Hand-Tufted (HT) HT550

Construction:	Hand-Tufted	ISO 2424
Yarn Content:	100% New Zealand Wool	ISO 2424
	Moth proof treated	
Dye Method:	Skein Dyed	
Yarns:	1/82 Dewsberry Count Z-twist	
Size & Shape:	Custom	
Total Weight:	4167 g/m ² 123 oz/yard ²	ISO 8543
Total Pile Weight:	2982 g/m ² 88 oz/yard ²	ISO 2424
Total Thickness:	12.5 mm	
Number of Tufts:	470 /dm ² 39297 oz/yard ²	ISO 1763
Primary Backing:	Cotton Canvas	ISO 2424
	65% cotton / 35% polyester	
Secondary Backing:	Cotton Mesh	ISO 2424
	Natural Rubber Latex	
Effective Pile Thickness:	85 mm 0.33 in	ISO 1766

Performance

Flame Resistance: Passes BS 4790

All specifications subject to normal manufacturing tolerances.

Encore Hospitality flooring products are to be installed in full accordance with Encore's installation instructions and standard trade practices. A program of regular cleaning and maintenance is vital for retaining a high appearance level. Installation plus Care & Maintenance manuals can be downloaded at www.encorehospitalitycarpet.com