

Specification for Carpet Tile (IN-T) 24oz Loop Pile

Construction:	Infinity
Yarn Content:	100% SD Nylon
Dye Method:	Solution Dyed
Gauge:	1/10th
Modular Size:	24" x 24" (planks available upon request)
Yarn Weight Tufted:	24 oz
Stitch Rate:	12 SPI
Primary Backing:	100% Synthetic
ModFlex (Modular Back):	Vinyl with Fiberglass reinforcement
ModAire (Cushion Back):	Available upon request
Pile Height:	approx. 0.220"
Total Thickness:	ModFlex approx 0.310" ModAire approx 0.430"

Performance

Flame Resistance:	Passes DOC FF-1-70
Static Control:	Less than 3.5 KV
Flooring Radiant Panel:	Class 1 (ASTM 648)
Smoke Density:	Less than .450 (ASTM E622)

Warranties

Wear:	10 Year Limited
-------	-----------------

Tufted pile weight is based on material post production; pattern and shear amounts may alter final tufted pile weight.

All specifications subject to normal manufacturing tolerances.

Encore Hospitality flooring products are to be installed in full accordance with Encore's installation instructions and standard trade practices. A program of regular cleaning and maintenance is vital for retaining a high appearance level. Installation plus Care & Maintenance manuals can be downloaded at www.encorecarpet.net